

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (currently amended) An X-ray source comprising:

- an electron source for the emission of electrons in an electron beam,
  - a target for the emission of characteristic, substantially monochromatic X-rays in response to the incidence of the electrons of the electron beam onto said target, said target comprising a metal foil of a thickness of ~~less than 10~~ between one and three  $\mu\text{m}$  and a base arrangement for carrying said metal foil, wherein the metal of said metal foil has a high atomic number allowing the generation of high intensity bremsstrahlung X-rays in a direction of transmission of the electron beam and generation of low intensity bremsstrahlung X-rays in a direction of reflection from said target and the material substantially included in the base arrangement has a low atomic number not allowing the generation of X-rays, and
  - an outcoupling means, which generally only transmits X-rays propagating in the reflection direction of the metal foil over an angular range of  $\pm 20^\circ$  antiparallel to the incident direction of the electron beam, for outcoupling a background of the low-intensity bremsstrahlung X-rays on which quasi-monochromatic characteristic lines of the metal foil are superimposed resulting in a quasi-monochromatic spectrum of X-rays on the side of the metal foil on which the electrons are incident and which is opposite to the side of the base arrangement,
- wherein said base arrangement comprises a rotatable base plate of a material having an atomic number of less than 10.

2. (canceled)

3. (previously presented) The X-ray source as claimed in claim 1, wherein said base arrangement comprises a cooling circuit arranged to allow a coolant to flow along the side of said metal foil opposite to the side on which the electrons are incident.

4. (previously presented) The X-ray source as claimed in claim 3, wherein the coolant has a mean atomic number of less than 10.

5. (previously presented) The X-ray source as claimed in claim 3, wherein the coolant is water.

6. (previously presented) The X-ray source as claimed in claim 3, wherein said cooling circuit comprises a constriction in the area of the metal foil.

7. (previously presented) The X-ray source as claimed in claim 3, wherein said target further comprises a carrier of low atomic number material supporting the metal foil on the side facing the coolant.

8. (canceled)

9. (previously presented) The X-ray source as claimed in claim 1, wherein the metal of said metal foil has an atomic number between 40 and 80.

10. (currently amended) The X-ray source as claimed in claim 1, wherein said outcoupling means is adapted to outcouple X-rays at angles of an angular range from substantially ~~45° to 135°~~ 70° to 110°, to the surface of the metal foil.

11. (canceled)

12. (previously presented) The X-ray source as claimed in claim 1, wherein said electrons are directed onto the surface of said metal foil at a substantially 90° angle.

13. (previously presented) The X-ray source as claimed in claim 1, wherein said electron source is located outside the X-ray beam to be outcoupled, said X-ray source further comprising means for directing the electron beam onto the metal foil.

14. (currently amended) A target for use in an X-ray source for the generation of characteristic, substantially monochromatic X-rays in response to the incidence of electrons in an electron beam, said target comprising a metal foil of a thickness of ~~less than 10~~ between one and three µm and a base arrangement for carrying said metal foil, wherein the metal of said metal foil has a high atomic number allowing the generation of high intensity bremsstrahlung X-rays in a direction of transmission of the electron beam and generation of low intensity bremsstrahlung X-rays in a direction of reflection from said target and the material substantially included in the base arrangement has a low atomic number not allowing the generation of X-rays, and

wherein said base arrangement comprises a rotatable base plate of a material having an atomic number of less than 10, further wherein a background of the low-intensity bremsstrahlung X-rays on which quasi-monochromatic characteristic lines of the metal foil are superimposed results in a quasi-monochromatic spectrum of X-rays produced on the side of the metal foil on which the electrons are incident and which is opposite to the side of the base arrangement.

15. (currently amended) An X-ray source comprising:

- an electron source for the emission of electrons in an electron beam, and
- a target for the emission of substantially monochromatic X-rays in response to the incidence of the electrons of the electron beam onto said target, said target comprising a metal foil of a base arrangement, said metal foil of a thickness of

between one and three  $\mu\text{m}$ , said metal foil allowing the generation of high intensity bremsstrahlung X-rays in a direction of transmission of the electron beam and generation of low intensity bremsstrahlung X-rays in a direction of reflection from said target and the base member arrangement not allowing the generation of X-rays,

wherein said base arrangement comprises a cooling circuit to allow a coolant to flow along the side of said metal foil opposite to the side on which the electrons are incident, and

wherein said target further comprises a carrier having a mean atomic number of less than 10 supporting the metal foil on the side facing the coolant, further wherein a background of the low-intensity bremsstrahlung X-rays on which quasi-monochromatic characteristic lines of the metal foil are superimposed results in a quasi-monochromatic spectrum of X-rays produced on the side of the metal foil on which the electrons are incident and which is opposite to the side of the base arrangement.

16. (canceled)

17. (previously presented) The x-ray source as claimed in claim 15, wherein the coolant is water.

18. (previously presented) The x-ray source as claimed in claim 15, wherein said cooling circuit comprises a constriction proximate the metal foil.

19. (canceled)

20. (currently amended) The X-ray source as claimed in claim 1, wherein said outcoupling means is adapted to outcouple X-rays in a direction at an angle in the range from ~~150° to 210°~~ 160° to 180° to the direction of incidence of said electrons.